


a **xylem** brand



D-237E


JOB:	REPRESENTATIVE:	
UNIT TAG:	ORDER NO.	DATE:
ENGINEER:	SUBMITTED BY:	DATE:
CONTRACTOR:	APPROVED BY:	DATE:


SHOWN WITH OPTIONAL PANEL



## 3 Pump 70M Series **Pressure Booster System Vetical Configuration**

DESIGN DATA:	System Capacity:  Pressure Required @ Discharge Header:  Pressure Drop through Package (include PRV):  Minimum Suction Pressure:				GPM PSIG PSIG PSIG		
	Gallons per M	linute	Pun	np No. 1	Pump No. 2	Pump No. 3	
PUMP DATA:	Pump TDH (fe Header size	eet) <sup>*</sup>					
	□ PRV	☐ Check Valve	Size				
<b></b>	Series Motor HP	1531	Size				
	Motor RPM	Volta	ige	_ Hertz_		Phase	
	*Note: TDH inclu	des PRV and package losse	s.				
STANDARD EQUIPMENT:	Assembled System. Basic unit fully piped, tested and mounted on steel frame includes: Bronze-fitted B&G pumps; shut-off valves on suction and discharge of each pump; combination pressure reducing-nonslam check valves on discharge side of each pump; thermal protection in discharge header. Headers and interconnecting piping are Type L copper.						





Panel Included

Yes (See Bulletin D-216)

No

END CAP LOCATION
(Based on facing front panel)

Both right, as shown

Both left

Suction Left, Discharge right

Suction right, discharge left

Dimensions Valid for 3" and 4" Headers only.

Do not use for construction. Dimensions are approximate and subject to change.

Contact factory for certified dimensions.

Note: Consult factory for 4-6 pumps application.

Xylem Inc. 8200 N. Austin Avenue Morton Grove, IL 60053 Phone: (847)966-3700 Fax: (847)965-8379 www.bellgossett.com

Bell & Gossett is a trademark of Xylem Inc. or one of its subsidiaries. © 2013 Xylem Inc.

