



Suction Can Selection Data

200.C.11 *(Effective June 1, 2006)*

Nominal Bowl Diameter	Barrel Diameter									
	8	10	12	14	16	18	20	24	30	36
5	448	892								
6	337	767								
7		603	1120	1486						
8		450	765	1372						
9			753	1115	1761	2490				
10			315	922	1620	2407				
11				625	1272	2001	2849			
12				382	1080	1867	2767			
13-14					450	1237	2137	4230		
15						877	1777	3870	7717	
16							1395	3487	7335	
18								2655	6502	
20								1732	5580	10327

Recommended capacity based on a fluid velocity of 5 ft./sec. For different fluid velocity ft./sec., contact factory. For larger can size, contact factory.

Suction Can Selection Data

200.C.11 *(Effective June 1, 2006)*

Can Weights

Can Diameter	First 5 Feet	Additional Feet
8	275	30
10	325	40
12	425	50
14	500	55
16	600	65
18	650	75
20	750	80
24	1000	95
30	1600	120
36	2100	145
42	2850	170
48	4000	200

Xylem Inc.

www.bellgossett.com

Bell & Gossett is a trademark of Xylem Inc. or one of its subsidiaries.

© 2017 Xylem Inc. BGD200C11 R1 July 2017



Bell & Gossett

a xylem brand